

WTPA 2.6 Truck Rules

1. Maximum Weight 8000#
2. OEM Chassis is mandatory. The vehicle must retain the full OEM Chassis, wheel tubs, back half conversions, and tube Chassis are prohibited. Must retain factory OEM wheelbase for year make and model of body, not to exceed 172" crew cab long box.
3. The body must be OEM truck body including the full bed floor. No flatbeds permitted. The body must retain the full sheet metal. After market hoods permitted. The hood must be closed and securely latched when hooked to sled.
4. Complete engine must have stock appearance except where otherwise noted in these rules. Maximum engine size will be 460ci. Engine must be in OEM location for the body used. Engine must have a 3/8 diameter cable surrounding the engine block. Cable is to be positioned between #1 and #2 cylinders and is to pass through manifolds. Cable will have 4 inches of slack. 4" cable clamps at cable splice are required. 1/4" aluminum or 1/8" steel-side shields on inline motors only must be mounted to frame along motor.
5. Cylinder head must be OEM or OEM replica for brand of engine. Outside of cylinder head must measure factory width and length. No billet heads of any material. Head must retain factory OEM valve angle. No deck plates permitted.
6. Hook point to be no closer than 44" of centerline of rear axle. Maximum hitch height of 24" with a minimum of 3.75" x 3" opening. Hitch must be stationary in all directions. Hitch must be frame mounted. Hitch must be centerline of rear axle or behind. Hitch must not exceed 25-degree angle from pivot point to hook point. No hitch supports or adjusters fastened to rear axle housing shall be above center point of rear axle. Pivot pin of drawbar can be no further forward than the centerline of rear axle.
7. Turbo is limited to a 2.6" inducer bore. Bore must be smooth. No MAP width enhancement groove (MWE) allowed. Compressor wheel must protrude into 2.6" bore for 1/8". Bore will be checked with a 2.605" turbo plug. Plug must not be able to enter inducer bore and contact wheel.

8. All vehicles must be equipped with upward pointing exhaust located either directly behind cab or out of truck hood. Two 3/8-inch diameter bolts must be placed through the exhaust pipe in a cross pattern within one inch of each other and within 12 inches of turbo. (6 inches preferred) In the horizontal pipe.
9. Front hanging weights are allowed, not to exceed 60 inches forward from the centerline of front axle. Ballast may be added in the bed of truck but must be securely fastened. Maximum weight 8000 pounds.
10. All trucks must have at least six-inch-wide u-joint shield around the rear u-joint constructed of at least 5/16 inch steel or 3/8 aluminum that will safely contain the u-joint and the end of the driveshaft. All shields must be securely mounted to vehicle. Any front shaft u-joints that can be visibly seen from side of truck must be shielded to contain the u-joint and the end of the driveshaft. Plus tethers straps.
11. A fire extinguisher system is permitted. 2.5# fire extinguisher must be securely mounted within reach of driver. A complete OEM firewall is required.
12. All drivers must have valid driver license and full Snell 2000 helmet, gloves, neck brace, shoes, headsock and SFI fire suit. Seatbelt/restraint must be worn.
13. The complete OEM floor pan is mandatory. Vehicle must maintain a complete firewall. Additional gauges and pillar pods are permitted.
14. Hand throttle permitted. Diesel fuel only (See fuels page for specs). No propane or NO2 or any other oxygen enhancers allowed. Foot throttles need a toe catch or toe loop.
15. Maximum of one P pump up to P7100 allowed. 13MM plunger limit. Ag governors permitted. The use of multiple high-pressure common rail fuel pumps is legal.
16. OEM rear and front ends required. Must have come factory in a one ton or smaller vehicle.
17. Axle shields are required. Shield to be .060" thickness steel or aluminum. A hole may be cut in one shield to allow operation of hub lock. (Page 65, Paragraph 5)
18. Safety switch (rain cap or guillotine) must shut off air to diesel engines. Switch will be securely mounted to back of vehicle. A 2 inch or bigger solid ring must be

attached to end of switch. Ring must be zip tied to switch bracket. Switch must also be able to be activated in cab while driver is secured in vehicle. Electric fuel pump also. 3-way dump valve on mechanical pumps.

19. Hydraulic steering permitted.

20. Suspension (Rear) – The upper mounting point for strut assembly must be in factory location. Adjustable caster/camber pillow ball mounts are permitted. The lower control arm may be strengthened provided the factory mounting points are maintained. Strut tower braces, lower tie bars, sway bars, and limit straps are permitted. Traction bars and devices are permitted. Raising or lowering of vehicle height with suspension modifications is permitted but must be bolt on only. Welds permitted for attachment to frame and axle only. Blocked suspension permitted. No airbags. Rear suspension may be made solid.

21. Tires must be DOT approved with maximum size of 35x12.50. No studded tires or tire chains. No alterations to tires permitted. No bar or terra tires. No sipping of tires.

22. Dual wheels are prohibited.

23. OEM transmission and transfer case must be used. Must have come factory in a one ton or smaller vehicle.

24. Non-OEM transmissions prohibited. Aftermarket torque convertors, valve bodies, and internal components are permitted.

25. SFI Bell housing and/or SFI blow proof bell housing (SFI 6.2 or 6.3 SFI 4.1) or SFI 6 strap blanket type shield must be used on automatics. SFI Bell housing must have sticker and SFI Blanket must have I.D. Tag.

26. Water injection is prohibited.

27. Air to Air intercooler only. No cooling device allowed for intercooler. No ice boxes.

28. No tinted windows (Front Sides or Front Window).

29. All vehicles will be towed in pits. No driving to scale or trailer. Tow-vehicles are provided.